




Prema DIN 46235  
Materijal: E-bakar DIN 40500  
Površina: cinkovana



Koriste se za završavanje Cu provodnika (VDE 0295) i užadi (DIN 48201) u energetskim kablovima i povezivanje u el. kolo pomoću vijka i navrtke. Imaju kontrolni otvor.



Na zahtev kupca izrađujemo i specijalne konstrukcije papučica.

Kodni broj	Oznaka mm/Vijak M	d2 mm	d1 mm	d3 mm	L1 mm	b mm	Broj presavijanja met./hidr.	Pokretanje kon	Izdrž g/100 km
700605	FCPCu-6/5	5,3	3,8	5,5	24	8,5	2/-	200	0,50
700606	FCPCu-6/6	6,4	3,8	5,5	24	8,5	2/-	200	0,50
701005	FCPCu-10/5	5,3	4,5	6,0	27	9,0	2/-	200	0,56
701006	FCPCu-10/6	6,4	4,5	6,0	27	9,0	2/-	200	0,56
701608	FCPCu-16/8	8,4	5,5	8,5	36	13,0	2/-	100	1,19
701610	FCPCu-16/10	10,5	5,5	8,5	36	17,0	2/-	100	1,19
701612	FCPCu-16/12	13,0	5,5	8,5	36	19,0	2/-	100	1,21
702508	FCPCu-25/8	8,4	7,0	10,0	38	16,0	2/-	100	1,62
702510	FCPCu-25/10	10,5	7,0	10,0	38	17,0	2/-	100	1,65
702512	FCPCu-25/12	13,0	7,0	10,0	38	19,0	2/-	100	1,68
703508	FCPCu-35/8	8,4	8,2	12,5	42	17,0	2/1	100	2,75
703510	FCPCu-35/10	10,5	8,2	12,5	42	19,0	2/1	100	2,75
703512	FCPCu-35/12	13,0	8,2	12,5	42	21,0	2/1	100	2,75
703516	FCPCu-35/16	17,0	8,2	12,5	42	21,7	2/1	100	2,75
705008	FCPCu-50/8	8,4	10,0	14,5	52	20,0	3/1	100	4,40
705010	FCPCu-50/10	10,5	10,0	14,5	52	22,0	3/1	100	4,40
705012	FCPCu-50/12	13,0	10,0	14,5	52	24,0	3/1	100	4,40
707008	FCPCu-70/8	8,4	11,5	16,5	55	24,0	3/1	100	6,00
707010	FCPCu-70/10	10,5	11,5	16,5	55	24,0	3/1	100	6,00
707012	FCPCu-70/12	13,0	11,5	16,5	55	24,0	3/1	100	6,00
707016	FCPCu-70/16	17,0	11,5	16,5	55	30,0	3/1	100	6,00
709508	FCPCu-95/8	8,4	13,5	19,0	65	28,0	4/2	50	8,70
709510	FCPCu-95/10	10,5	13,5	19,0	65	28,0	4/2	50	8,70
709512	FCPCu-95/12	13,0	13,5	19,0	65	28,0	4/2	50	8,70
709516	FCPCu-95/16	17,0	13,5	19,0	65	32,0	4/2	50	8,70
712010	FCPCu-120/10	10,5	15,5	21,0	70	32,0	4/2	50	11,30
712012	FCPCu-120/12	13,0	15,5	21,0	70	32,0	4/2	50	11,30
712016	FCPCu-120/16	17,0	15,5	21,0	70	38,0	4/2	50	11,30
715012	FCPCu-150/12	13,0	17,0	23,5	78	34,0	4/2	75	16,10
715016	FCPCu-150/16	17,0	17,0	23,5	78	34,0	4/2	75	16,10
715020	FCPCu-150/20	21,0	17,0	23,5	78	40,0	4/2	75	16,10
718512	FCPCu-185/12	13,0	19,0	24,0	82	37,0	4/2	25	18,50
718516	FCPCu-185/16	17,0	19,0	25,5	82	37,0	4/2	25	18,50
718520	FCPCu-185/20	21,0	19,0	25,5	82	40,0	4/2	25	18,50
724010	FCPCu-240/10	10,5	21,0	29,0	92	42,0	-/2	25	27,00
724012	FCPCu-240/12	13,0	21,5	29,0	92	42,0	-/2	25	27,00
724016	FCPCu-240/16	17,0	21,5	29,0	92	42,0	-/2	25	27,00
724020	FCPCu-240/20	21,0	21,5	29,0	92	45,0	-/2	25	27,00
730016	FCPCu-300/16	17,0	24,5	32,0	100	48,0	-/2	20	34,00
730020	FCPCu-300/20	21,0	24,5	32,0	100	48,0	-/2	20	34,00
740012	FCPCu-400/12	13,0	27,5	38,5	115	55,0	-/3	10	68,00
740016	FCPCu-400/16	17,0	27,5	38,5	115	55,0	-/3	10	69,00
740020	FCPCu-400/20	21,0	27,5	38,5	115	55,0	-/3	10	65,40
750016	FCPCu-500/16	17,0	31,0	42,0	125	60,0	-/3	10	83,00
750020	FCPCu-500/20	21,0	31,0	42,0	125	60,0	-/3	10	82,00
750024	FCPCu-500/24	25,0	31,0	42,0	125	60,0	-/3	10	80,00
763016	FCPCu-630/16	17,0	34,5	44,0	135	60,0	-/4	10	79,60
763020	FCPCu-630/20	21,0	34,5	44,0	135	60,0	-/4	10	78,70