

Vijačne kablovske papučice

Koriste se za završavanje Cu provodnika i energetskih kablova (bez upotrebe prese), prema SRPS N.F4.101. Zaštita od korozije je izvršena galvanskim cinkovanjem.

| Kodni broj | Oznaka mm ² /Vijak M | d1 mm | d2 mm | L1 mm | L2 mm | Pakovanje kom | Težina g/100kom |
|------------|---------------------------------|-------|-----------|-------|-------|---------------|-----------------|
| 3601006 | FPV-10/6 | 6,5 | 3,8 | 33 | 19 | 200 | 1,00 |
| 3601606 | FPV-16/6 | 6,5 | 5,8-5,3 | 38 | 21 | 200 | 1,60 |
| 3602508 | FPV-25/8 | 8,5 | 5,3-6,7 | 42 | 23 | 200 | 2,20 |
| 3603508 | FPV-35/8 | 8,5 | 6,7-8 | 48 | 24 | 100 | 3,30 |
| 3603510 | FPV-35/10 | 10,5 | 6,7-8 | 57 | 24 | 100 | 3,50 |
| 3605010 | FPV-50/10 | 10,5 | 8-9 | 57 | 28 | 100 | 4,60 |
| 3607010 | FPV-70/10 | 10,5 | 9-10,5 | 60 | 30 | 100 | 6,00 |
| 3609512 | FPV-95/12 | 13,0 | 10,5-13,5 | 69 | 32 | 50 | 8,50 |
| 3612012 | FPV-120/12 | 13,0 | 13,5-15 | 72 | 40 | 50 | 16,00 |
| 3612012 | FPV-150/12 | 13,0 | 15-16,5 | 80 | 42 | 25 | 19,90 |
| 3615016 | FPV-150/16 | 17,0 | 15-16,5 | 80 | 42 | 25 | 19,80 |

