

## Technical Specifications

Contact:	SPDT
Contact Material:	AgSnO <sub>2</sub>
Rated Current:	6A
Max. Switching Current:	10A
Max. Switching Voltage:	400V AC
Max. Switching Power:	1500VA
Creepage/Clearance:	6/8mm
Operate/Release Time:	10/5ms
Testing Voltage	
Coil/Contact:	4000V <sub>rms</sub>
Opening Contact:	1000V <sub>rms</sub>
Lifetime	
Mechanical:	10x10 <sup>6</sup> Operations
Electrical (5A/250V AC):	10x10 <sup>3</sup> Operations
Operating Temperature:	-40...+85°C
Weight Approx.:	6g

## Coil Data

U <sub>N</sub>	U <sub>A<sub>N</sub></sub>	U <sub>A<sub>b</sub></sub>	P <sub>N</sub>	R <sub>N</sub>
[V DC]	[V]	[V]	[mW]	[W]
24	16,8	1,2	170	3390

U<sub>N</sub> = Rated Voltage, U<sub>A<sub>N</sub></sub> = Operate Voltage, U<sub>A<sub>b</sub></sub> = Release Voltage, P<sub>N</sub> = Rated Power, R<sub>N</sub> = Coil Resistance; All Specifications Measured at 23°C