



Relay type	Voltage of the coil (V)	Socket type	Resistance of the coil (Ω)	Number of contacts	Packing/Box (pcs)	Catalogue number
ELM - 55.02	12 VDC	ELM - RT702-B	42	2NO+2NC	50 / 500	<b>57521</b>
ELM - 55.02	24 VDC	ELM - RT702-B	168	2NO+2NC	50 / 500	<b>57522</b>
ELM - 55.02	48 VDC	ELM - RT702-B	675	2NO+2NC	50 / 500	<b>57523</b>
ELM - 55.02	230 VAC	ELM - RT702-B	14000	2NO+2NC	50 / 500	<b>57525</b>
ELM55.02	24VAC	ELM - RT702-B		2NO+2NC	50/500	<b>57526</b>
ELM - 55.04	12 VDC	ELM-RT704-B	42	4NO+4NC	50 / 500	<b>57541</b>
ELM - 55.04	24 VDC	ELM-RT704-B	168	4NO+4NC	50 / 500	<b>57542</b>
ELM - 55.04	48 VDC	ELM-RT704-B	675	4NO+4NC	50 / 500	<b>57543</b>
ELM - 55.04	110 VAC	ELM-RT704-B	3500	4NO+4NC	50 / 500	<b>57544</b>
ELM - 55.04	230 VAC	ELM-RT704-B	14000	4NO+4NC	50 / 500	<b>57545</b>
ELM-55.04	24VAC	ELM-RT704-B		4NO+4NC	50/500	<b>57546</b>



57901 57902, 57912

Socket type	Dimensions (mm)	Number of terminals (pcs.)	Packing/Box (pcs)	Catalogue number
ELM - RT624-B	76 x 15	5	20 / 600	<b>57901</b>
ELM - RT702-B	76 x 27	11	10 / 240	<b>57902</b>
ELM - RT704-B	76 x 27	14	10 / 240	<b>57912</b>
ELM - 90.22	68 x 38	8	10 / 400	<b>57904</b>
ELM - 90.23	68 x 38	11	10 / 400	<b>57905</b>



57904, 57905