

KATEGORIJE

[Alati, kutije, setovi](#)[Conrad](#)[Detektori i testeri kablova](#)[Generatori](#)[Kablovi & oprema](#)[Kalajno kupatilo](#)[Klešta za kablove](#)[Krimp klešta](#)[Laboratorijska napajanja](#)[Laseri i uređaji za nivelisanje](#)[Lemne stanice](#)[Lupe i uveličavajuća stakla](#)[Merenje neelektričnih veličina](#)**Multimetri**[Organizeri](#)[Osciloskopi](#)[Pincete](#)[Pribor za lemljenje](#)[Ručice za lemljenje](#)[Skidači izolacije](#)[Specijalni termometri](#)[Štapne lemilice](#)[Strujna klešta](#)[Testeri](#)[Uređaj za usisavanje dima](#)[Vakuum pumpe](#)

NA LAGERU

Odmah dostupan (155)



Multimetar UNI-T UT131C

1,888.00 дин.

- 1 +

DODAJ U KORPU

ZATRAŽITE PONUDU

Šifra proizvoda: 07720229

Kategorija: Multimetri

Oznaka: Odmah dostupan



OPIS

AC voltage measuring – 200 V / 250 V
 DC voltage measuring – 200 mV / 250 V
 DC current measuring – 200.0 μ A / 10.00 A
 Resistance measuring – 200.0 Ω / 20.0 M Ω
 Temperature measuring: -40°C to +250°C
 Continuity test (buzzer)
 Diode test
 Manual range selection
 Reversed polarity detection
 Data hold function
 Display backlight
 Automatic shutdown after being idle for 15 min
 Test leads and K-thermocouple included
 Low battery indication
 Overload protection, fuse protected

Technical parameters:

AC voltage measuring (range, resolution, accuracy) :

200.00 V / 0.1 V / $\pm 1.2\% + 3$ 250 V / 1 V / $\pm 1.2\% + 3$

DC voltage measuring (range, resolution, accuracy) :

200 mV / 0.1 mV / $\pm 0.7\% + 3$ 2000 mV / 1 mV / $\pm 0.5\% + 2$ 20.00 V / 0.01 V / $\pm 0.7\% + 3$ 200.0 V / 0.1 V / $\pm 0.7\% + 3$ 250 V / 1 V / $\pm 0.7\% + 3$

DC current measuring (range, resolution, accuracy) :

2000.0 μ A / 1 μ A / $\pm 1.0\% + 2$ 20.0 mA / 0.01 mA / $\pm 1.0\% + 2$ 200.0 mA / 0.1 mA / $\pm 1.0\% + 2$ 10.00 A / 0.01 A / $\pm 1.2\% + 5$

Resistance measuring (range, resolution, accuracy) :

200.0 Ω / 0.1 Ω / $\pm 1.0\% + 2$ 2000 Ω / 1 Ω / $\pm 0.8\% + 2$ 20.00 k Ω / 0.01 k Ω / $\pm 0.8\% + 2$ 200.0 k Ω / 0.1 k Ω / $\pm 0.8\% + 2$ 20.00 M Ω / 0.01 M Ω / $\pm 1.2\% + 3$

Multimeter conforms to IEC 61010-1, IEC 61010-2-030, CAT II

Dimensions (mm) : 134 x 77 x 47

Power supply : 2 x AAA 1.5 V batteries (included)

Weight : cca 206 g (with batteries)

Operating temperature : 0 – 40°C

POVEZANI PROIZVODI



MULTIMETRI
 Multimetar UNI-T UT118B
 – PEN TYPE
4,446.00 дин.



MULTIMETRI
 Multimetar UNI-T UT 70B
12,199.00 дин.



MULTIMETRI
 Multimetar UNI-T UT139A
6,412.00 дин.



MULTIMETRI
 Multimetar UNI-T UT131A
2,777.00 дин.

O NAMA

San-Working Electronics doo je baziran na kataloškoj online prodaji mernih uređaja, lemilica, alata, razvojnih okruženja itd...



PRIJAVITE SE NA NAŠ NEWSLETTER

Email

PRIJAVA

KONTAKT

San-Working Electronics

Telefon: 063/7747-826

Email: office@sanelectronics.rs
 sanworkingelectronics@gmail.com

PIB: 110814097, Mat.Br: 21389811
 Račun: 160-512347-97 Banca Intesa