

Function	Range	Resolution	Accuracy
DC Voltage	500mV	0.01mV	± (1.0 % ± 8 Digits)
	5V	0.0001V	
	50V	0.001V	
	500V	0.01V	
	600V	0.1V	

Function	Range	Resolution	Accuracy
AC Voltage True RMS (50Hz to 1000Hz)	500mV	0.01mV	± (1.0 % ± 30 Digits)
	5V	0.0001V	
	50V	0.001V	
	500V	0.01V	
	600V	0.1V	

All AC Voltage Range are specified from 5% of range to 100% of range

Function	Range	Resolution	Accuracy
Resistance	500	0.01	± (1.0 % ± 9 Digits)
	5 K	0.0001 K	
	50 K	0.001 K	
	500 K	0.01 K	± (1.0 % ± 5 Digits)
	5 M	0.1 K	
	50 M	1 K	

Function	Range	Resolution	Accuracy
Capacitance	500nF	0.01nF	± (3.5 % ± 40 Digits)
	5000nF	0.1 nF	
	50uF	0.01uF	± (3.5 % ± 10 Digits)
	500uF	0.1 uF	
	5mF	0.001mF	

Function	Range	Resolution	Accuracy
Frequency	50Hz		± (0.3 % ± 2 Digits)
	500Hz		
	5kHz		
	50kHz		
	500kHz		
	5MHz		
10MHz			

Function	Range	Resolution	Accuracy
Duty Cycle	5 to 95 %	0.1%	± (1.0 % ± 2 Digits)

Pulse Width: 100uS - 100mS, Frequency: 10Hz to 10kHz

Function	Range	Resolution	Accuracy
Temperature (type-K) (probe accuracy not included)	-100 to 1000°C	0.1°C	± (1.0 % ± 2.5°C)
	-148 to 1832°F	0.1°F	± (1.0 % ± 4.5°F)

INCLUDED ACCESSORIES:

- Testing Leads
- Test Certificate
- Soft Carrying Case
- Instruction Manual
- Temperature Probe
- Battery

